

Declaration of Performance

No. CASEA-114 735

Material

Lightweight rendering/plastering mortar LW

Product Name

bauprotec FLP Plus

Intended Use

Plastering of ceilings and walls inside and outside of buildings

Producer

CASEA GmbH, Pontelstrasse 3, 99755 ELLRICH, GERMANY

System of Assessment and Verification of Constancy of Performance

System 4

Declared Performance

Test Parameter	Performance	Harmonized Technical Specification
Reaction to fire	A1	EN 998 -1: 2016
Compressive strength	CS II	EN 998 -1: 2016
Capillary water absorption	W1	EN 998 -1: 2016
Water vapour permeability coefficient	$\mu \leq 15$	EN 998 -1: 2016
Adhesion	$\geq 0,08$ N/mm ² FP: A, B or C	EN 998 -1: 2016
Thermal conductivity (Tabulated value)	$\lambda_{10, \text{dry, mat}} \leq 0,18$ W/(mK) @ P=50% $\lambda_{10, \text{dry, mat}} \leq 0,20$ W/(mK) @ P=90%	EN 998 -1: 2016
Durability	NPD	EN 998 -1: 2016
Dangerous Substances	NPD	EN 998 -1: 2016

THIS DOCUMENT HAS BEEN DEVELOPED UNDER THE GUIDELINES OF ANNEX ZA1. 2003/EN 998-1 AND USED TO DEFINE CONFORMITY OF PRODUCTS AND CONTAINS 2 PAGES.

The manufacturer assumes the responsibility for the conformity of the construction product with the declared performance.

Andreas Hübner – Manager Product Management


(Name and Title)

Ellrich, 01th of January 2017 _____
(Place and Date)


(Signed)

Enclosed:
Material Safety Data Sheet

CE-Marking: bauprotec FLP plus

	
CASEA GmbH Pontelstr.3 99755 Ellrich Germany	
10	
CASEA-114 735	
EN 998-1	
Lightweight rendering/plastering mortar LW Plastering of ceilings and walls inside and outside of buildings	
Reaction to fire	A1
Compressive strength	CS II
Capillary water absorption	W1
Water vapour permeability coefficient	$\mu \leq 15$
Adhesion	$\geq 0,08 \text{ N/mm}^2$ FP A,B or C
Thermal conductivity (Tabulated value)	$\lambda_{10, \text{dry,mat}} \leq 0,18 \text{ W/(mK)}$ @ P=50% $\lambda_{10, \text{dry,mat}} \leq 0,20 \text{ W/(mK)}$ @ P=90%
Durability	NPD
Dangerous Substances	NPD

NPD: No Performance Determined